

# T3 Bunded & Portable Diesel Tanks

www.transworldequipment.com



## Standard Features

<u>Nom. Capacity</u>	<u>Tare</u>	<u>MGW</u>
22,000 ltr (5812 USgal)	3,900 kg	34,000 kg
Working Pressure:	4 bar (58 psi)	0.41 bar allowable vacuum
Test Pressure:	6 Bar (87 psi)	
ISO Dimensions:	L6058mm x W2048mm x H2591mm (20' x 8' x 8' 6")	
Structural Materials:	MNR 16N	
Bund System:	Cavity wall capacity to high level	
Approvals:	UN coded T3, RID/ADR, USDOT, AAR 600, UIC, TIR	

## UNIQUE DESIGN FEATURES

- \* Patented Frame Design
- \* Inset end for fitment of equipment
- \* Drip Tray
- \* Dynamic Test 8g
- \* USDOT approved
- \* Level gauge
- \* Storage and transport in one



Fit standard equipment  
or your metering system  
here

## Standard Equipment (Fortvale or Customers Choice)

Manway:	500mm Dia.
Pressure Device:	2 1/2" Prevac
Discharge Valve:	High level to low -
Fill and Suction:	High level 1" for s
Overflow:	2" Safe Overflow
High Access:	Ladder and hame

Bulk Containers

20 ft and 40ft  
Full Opening  
Side Door  
Containers

Waste-  
management  
Containers

Open-top, GPs  
& Flatracks

LPG T50 tanks

27 tonne  
Bitumen tanks

28,000 ltr  
Lubricant &  
Oil Tanks

70 m3  
Petrochem  
storage Tanks

26,000 ltr  
tank containers

28,000 ltr  
Food tanks

P.O. Box 577  
Lincroft, NJ 07738-0577

Tel: 732-389-1836  
Fax: 732-389-1837

E-mail: sales@transworldequipment.com  
Website: transworldequipment.com

**TRANSWORLD**  
Equipment Corp.  
Intermodal Equipment Specialists

