

T50 UN Portable Tank

www.transworldequipment.com



Unique Design Features

- Propane Rated T50 (IMO-5) 18 bar LPG Tank
- TC Impact Approved
- Removable SS valve protection cabinet
- Ease of maintenance

Specification

Nom Capacity	24,000L	6340	US gal
MPGM	36000 kg	79365	lbs
Tare	9250 kg	20419	lbs
Length	6058 mm	20	ft
Width	2438 mm	8	ft
Height	2591 mm	8 ft 6	in
Maximum Allowable Working Pressure	18.0 bar	261.0	psig

Tank	- in accordance with:	IMDG, RID/ADR, ASME VIII DIV 1 – 2004
	- type:	T50 UN Portable Tank 6mm Ref MS thk
Frame	- in accordance with:	ISO 1496/3
	- type:	Beam Design

Standard Equipment

Manhole:	500mm ID
Relief Valve:	Fort Vale – 3" ID at +18,0 bar (+261,0 psig)
Gas Line:	Fort Vale – DN 50 (2") Conn 1¼" ACME
Liquid Line:	Fort Vale – DN 50 (2") Conn 3¼" ACME
Pressure Gauge:	0 - 30 bar graduation is fitted on the rear dished end
Valve Cabinet:	Stainless Steel bolted-on valve protection cabinet
Sunshield:	Marine grade aluminium, 2mm thick, 40mm from tank shell
Remote Control:	10m SS cable remote control, including fire safe fuses
Provision made for:	a thermometer and Rochester magnetic level gauge
Optional extras:	Walkways, Ladder, Temp & Level gauge

20ft and 40ft Full Opening Side Door Containers

Waste-management Containers

Open-top, GPs & Flatracks

LPG T50 tanks

27 tonne Bitumen tanks

28,000 ltr Lubricant & Oil Tanks

70 m3 Petrochem storage Tanks

26,000 ltr tank containers

28,000 ltr Food tanks

P.O. Box 577
Lincroft, NJ 07738-0577

Tel: 732-389-1836
Fax: 732-389-1837

E-mail: sales@transworldequipment.com
Website: transworldequipment.com

TRANSWORLD
Equipment Corp.
Intermodal Equipment Specialists

