



## 2023 53FT AIR RIDE VAN TRAILER

INCLUDES HOLLAND 1/4 KING PIN, W/46 11/16" WIDE COMPOSITE PANEL WALLS, SPARE TIRE HOLDER, ONE PIECE ROOF, DOT LIGHTS, REAR RUBBER STOPS, REFLECTIVE TAPE, POSTS AT 48", DEFLECTORS INCLUDED

# SPECIFICATIONS

<b>DIMENSIONS</b>	53 FT, Height 13.5 FT, Width 8.53 FT	<b>COMPONENTS</b>	1/4" thick lower front plate.
<b>CAPACITY</b>	Load capacity by design 30 Ton. Evenly distributed. Lower and upper rails STD 10.5		Pull plate in 1/4" Domexx caliber with crossmembers on the back between pull plate and landing gear.
<b>ABS</b>	ABS 2S/1 M without diagnostics tool		King Pin Holland 1/4
<b>BRAKES</b>	Haldex type 30/30 16.5" x 7".	<b>DUMP VALVE</b>	Automatic dumpo valve AKHD-203-3
<b>FLOORING</b>	Laminated hardwood RADWOOD, with anti-skid sheet protection at the door entrance. At 20 1/4 in cal.10.	<b>ELECTRICAL</b>	One piece sealed harness
<b>LANDING GEAR</b>	Holland Mark V	<b>FRAME</b>	Side lower rails and front lower rail aluminum 10 1/2". Upper rail aluminum 10.5"
<b>BUMPER</b>	DOT rear bumper	<b>SUSPENSION</b>	Air Ride
<b>DOORS</b>	Composite swing doors (composite panel 12mm) with 2 cam type lock on left door and two on right door and 5 hinges per door .	<b>AXLES</b>	(2) Rockwell, 30,000 LBS
<b>WALLS</b>	Composite panel side walls, white at front, with white pre-painted aluminum sheet as lining	<b>WHEELS</b>	Steel 22.5
<b>INNERLINING</b>	Galvanized steel inner lining gauge 18, 12" high all around	<b>TIRES</b>	295/75 22.5
<b>ROOF</b>	19-gauge one-piece aluminum roof with 12" arches in the front and 24" in the back. Omega-type roof arch of 98 3/8 cal.16 high-strength galvanized steel.	<b>COLOR</b>	White
<b>CROSSMEMBERS</b>	4 inch "I" beam crossmembers set at 12 "spacing , on landing gear and bays at 6" and 12" on the suspension	<b>SPARE TIRE HOLDER</b>	One included



**Photos**

